

Scissor Lift

MODEL	58SL	610SL	610SLTA	612SLTA	7812SLTA
LENGTH	8'	10'	10'	12'	12'
WIDTH	5'	6'	6'	6'	78"
FLOOR HEIGHT	14"	14"	14"	14"	14"
AXLE					
QUANTITY	Single	Single	Tandem	Tandem	Tandem
CAPACITY	5200 Drop	5200 Drop	5200 Drop	5200 Drop	5200 Drop
TYPE	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring	Leaf Spring
BEARING LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE
BRAKES	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
BREAKAWAY KIT	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
TIRE SIZE	ST225R15	ST225R15	ST225R15	ST225R15	ST225R15
TIRE LOAD RANGE	D	D	D	D	D
WHEEL BOLT PATTERN	6 – 5 1/2	6 – 5 1/2	6 – 5 1/2	6 - 5 1/2	6 – 5 1/2
HITCH BALL SIZE	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
HITCH HEIGHT	19"	19"	19"	19"	19"
HITCH WEIGHT	90	115	165	190	220
CURB WEIGHT	900	1150	1650	1900	2200
GVWR	5200 lb.	5200 lb.	9990 lb.	9990 lb.	9990 lb.
PAYLOAD CAPACITY	4300	4050	8340	8090	7790
12 VOLT CONNECTION	7 WAY RV	7 WAY RV	7 WAY RV	7 WAY RV	7 WAY RV
LIGHTS					
STANDARD	SEALED	SEALED	SEALED	SEALED	SEALED
OPTIONAL*	L.E.D.*	L.E.D.*	L.E.D.*	L.E.D.*	L.E.D.*
RAMP SIZE/STYLE	5' FOLD-UP	5' FOLD-UP	5' FOLD-UP	5' FOLD-UP	5' FOLD-UP
FLOOR	1/8" STEEL	1/8" STEEL	1/8" STEEL	1/8" STEEL	1/8" STEEL
TIE-DOWNS	(4) D-Rings	(4) D-Rings	(4) D-Rings	(4) D-Rings	(4) D-Rings
FRONT JACK	DROPLEG	DROPLEG	DROPLEG	DROPLEG	DROPLEG
DOT LIGHTING	YES	YES	YES	YES	YES
SAFETY CHAINS	5/16" GR. 70	5/16" GR. 70	5/16" GR. 70	5/16" GR. 70	5/16" GR. 70
FENDERS					
STANDARD	STEEL	STEEL	STEEL	STEEL	STEEL

Specifications subject to change without notice