



Aluminum 14,000 Lb. Trailer



Shown with optional toolbox

Features:

Leaf Spring Axles
L.E.D. Lights
Treated Wood Floor
Electric Brakes

Radial Tires
Ramps: (Stand Up or Self Store)
Removable Tread Brite Fenders
Breakaway Kit



Some models may show optional equipment

See back of sheet for specifications

Aluminum 14K Trailers

<i>MODEL</i>	<i>AS20HD-14BT</i>	<i>AS22HD-14BT</i>	<i>AS24HD-14BT</i>
BED LENGTH	20'	22'	24'
BED WIDTH	82"	82"	82"
OVERALL LENGTH	23' 6"	25' 6"	27' 6"
OVERALL WIDTH	102"	102"	102"
FLOOR HEIGHT	28"	28"	28"
Floor to top of Fender	8"	8"	8"
AXLE QUANTITY CAPACITY TYPE	TANDEM 7,000 LB. Leaf Spring	TANDEM 7,000 LB. Leaf Spring	TANDEM 7,000 LB. Leaf Spring
BEARING LUBE	EZ-LUBE	EZ-LUBE	EZ-LUBE
BRAKES	4 WHEEL ELEC.	4 WHEEL ELEC.	4 WHEEL ELEC.
BREAKAWAY KIT	STANDARD	STANDARD	STANDARD
TIRE SIZE	ST235R16	ST235R16	ST235R16
TIRE LOAD RANGE	E	E	E
WHEEL BOLT PATTERN	8 – 6 1/2	8 – 6 1/2	8 – 6 1/2
HITCH BALL SIZE	2 5/16"	2 5/16"	2 5/16"
HITCH HEIGHT	ADJUSTABLE	ADJUSTABLE	ADJUSTABLE
HITCH WEIGHT	195	215	235
CURB WEIGHT	1950	2150	2350
GVWR	14,000	14,000	14,000
PAYLOAD CAPACITY	12,050	11,850	11,650
12 VOLT CONNECTION	7 WAY RV	7 WAY RV	7 WAY RV
FRAME MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM
CROSSMEMBERS	ALUMINUM	ALUMINUM	ALUMINUM
RAMP SIZE/STYLE	SELF STORE or STAND-UP	SELF STORE Or STAND-UP	SELF STORE Or STAND-UP
FLOOR	2 X 8 TREATED	2 X 8 TREATED	2 X 8 TREATED
TIE-DOWNS	Stake pockets	Stake pockets	Stake pockets
JACK	10K	10K	10K
DOT LIGHTING	Rubber Grommet	Rubber Grommet	Rubber Grommet
SAFETY CHAINS	3/8" GR. 70	3/8" GR. 70	3/8" GR. 70
FENDERS	10.75 X 72 X .100 ALUMINUM	10.75 X 72 X .100 ALUMINUM	10.75 X 72 X .100 ALUMINUM